

Exclusive Timeless and traditional



T2 ceiling accessories

The highly successful T2 ceiling accessories range maintains superb quality and easy to install technical specification that has established this design as a firm favourite.

The range includes polycarbonate and safety ceiling accessories.

Features & benefits:

- > Fully coordinated fully rated T2 range incorporates large footprint for easy installation together with raised mounting feet to assist installation on uneven surfaces
- > Ample wiring space with four knockouts
- > Clear terminals for easy visibility and installation
- > Batten holders and ceiling roses share a common base assembly with 50.8 mm fixing centres
- > Pendant lamp holder has integral cord grip to prevent cable pull on terminals
- > The range includes polycarbonate and lamp activated lampholders

Weatherproof

IP66 & IP55

Our weatherproof range are tough, durable options for outdoor or more arduous environments. Socket-outlet are IP66 or IP55 rated for even greater weather resistance.

Features & benefits:

Consumer

- > Smooth, curved aesthetic design
- > Manufactured from tough, durable thermoplastic
- > IP66 for maximum weatherproof protection whilst in use
- > IP55 for general outdoor weatherproof protection

Installer

- > Standard knockouts for 20 mm conduit entry with additional cut-out facility to convert to 25 mm conduit entry
- > IP66 socket-outlets accept standard 13 A plugs including moulded on plugs
- > Switches can be operated through membrane, thereby maintaining full IP rating

Exclusive

T2 ceiling accessories Dry lining boxes, plugs & adaptors



GABAT

Batten lampholder

- Clear terminals for easy visibility and installation
- Ample wiring space with four knockouts
- Large capacity earth terminal
- Pendant lamp holder has integral cord grip to prevent cable pull on terminals
- Batten lamp holders (straight and angled) are pre-wired
- BS EN 61184

Part number	Description
GBAT	Pre-wired batten-lampholder
GABAT	Pre-wired angled batten-lampholder



GEBAT

Fixed terminal batten holder & ceiling rose

- Raised mounting feet assist mounting on uneven surfaces
- Batten holders and ceiling roses share a common base assembly. Fixing centres are 50.8 mm
- Bases also include easy joist mounting facility
- BS EN 61184
- BS 67

Part number	Description
GEBAT	T2 batten holder 3 terminal
GRO	Ceiling rose
GROC	Clear base ceiling rose



GPEND6

Pendants & lampholder

- High heat resistance (T2 rated) to BS EN 61184:1995. (Batten holders & lamp holders only)
- Max lamp rating 150 W
- Plunger springs are enclosed in brass sleeves
- Zinc plated steel bayonet sleeve for durability
- BS EN 60598-2-1
- BS EN 61184

Part number	Description
GPEND6	Pre-wired 6" pendant
GPEND6C	Pre-wired 6" clear base pendant
GPEND9	Pre-wired 9" pendant
GPEND9C	Pre-wired 9" clear base pendant
GLHC	Lampholder with integral cord grip



TOP13A

Plugs & adaptors

- Uses fuse to BS 1361
- Round pin plugs unfused
- BS 1363 (13 A plugs)
- BS 546 (round pin plugs)

Part number	Description
TOP2AR	2 A round pin plug
TOP5AR	5 A round pin plug
TOP15AR	15 A round pin plug
TOP13A	Plug top fitted with 13 A fuse
ADAPT2W	2 way unfused adaptor
ADAPT3WF	3 way fused adaptor

Weatherproof IP66 / IP55



GWPIU3020

IP66 – 13 A socket-outlet

- IP66 maintained whilst in use
- BS 1363

Cat. no.	Description
GWPIU3050	1 gang unswitched
GWPIU3060	2 gang unswitched
GWPIU3020	2 gang switched
GWPIU3010	1 gang switched



GWP1632

IP55 – 10 AX switches

- BS EN 60669-1

Part number	Description
GWP1612	1 gang 2 way
GWP1622	2 gang 2 way
GWP1632	3 gang 2 way
GWP1614	1 gang intermediate



GWP2011

IP55 – 20 AX switches

- BS EN 60669-1

Part number	Description
GWP2010	DP
GWP2011	DP with neon



GWP3020

IP55 - 13 A socket-outlet

- BS 1363

Part number	Description
GWP3050*	1 gang unswitched
GWP3060*	2 gang unswitched
GWP3010*	1 gang switched
GWP3020*	2 gang switched

*IP4X whilst socket-outlet is in use